



MB2236adw

Small. Easy to use. Great value.

With monochrome output up to 36 pages per minute* and two-sided printing, the Lexmark MB2236adw offers both impressive performance and affordability. Standard Wi-Fi enhances connectivity and support for mobile users, while both its included fax and scanning are backed up by a 1-GHz processor and 512 MB of memory.

Get more done

- ▶ Print up to 36 pages per minute*, and scan up to 25 pages per minute.
- ▶ Tackle your printing workload with the power of a 1-GHz processor and 512 MB of memory.
- ▶ Unison™ Toner replacement cartridges deliver up to 6,000 pages** of high-quality printing.
- ▶ Load and print up to 250 pages without refilling, or manual-feed single sheets.
- ▶ Send and receive faxes with included analog fax.
- ▶ Use media sizes from A6 to legal in the paper tray, plus smaller media and envelopes in the manual feeder.

The right fit

- ▶ Compact dimensions of only 16.4 inches wide, 14.2 inches deep, and 13.9 inches tall (41.5 cm wide x 36 cm deep x 35.2 cm tall) helps it fit almost anywhere.
- ▶ Standard Wi-Fi supports desktop and mobile devices, and complements the MFP's ethernet and USB connections.
- ▶ The two-line LCD lets you configure, interact and monitor vital system information.



MB2236adw



Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.
- ▶ A range of embedded features harden device against attacks.

Built for planet earth

- ▶ Energy management features reduce power consumption in active use or sleep mode.
- ▶ Standard two-sided printing saves paper.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Program (LCCP).

*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous mono declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19752. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

Product specifications		Lexmark Black & White All-in-One 2-series (MB2236adw)	
Printing			
Display	2-line LCD display		
Print Speed: Up to ⁶	Black: 36 ppm		
Time to First Page: As fast as	Black: 8 seconds		
Print Resolution	Black: 1200 IQ (1200 x 600 dpi), 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi		
Memory	Standard: 512 MB / Maximum: 512 MB		
Hard Disk	Not Available		
Recommended Monthly Page Volume ²	250 - 2500 pages		
Maximum Monthly Duty Cycle: Up to ³	30000 pages per month		
Copying			
Copy Speed: Up to ⁶	Black: 36 cpm		
Time to First Copy: As fast as	Black: 8.5 seconds		
Scanning			
Scanner Type / ADF Scan	Flatbed scanner with automatic document feeder / One-sided automatic document feeder		
A4/Ltr Simplex Scan Speed: Up to	Black: 23 / 25 sides per minute / Color: 7 / 8 sides per minute		
ADF Paper Input Capacity: Up to	50 pages 20 lb or 75 gsm bond		
Faxing			
Modem Speed	Max is 33,600 bps, V.34 Half-Duplex Kbps		
Supplies ⁷			
Laser Cartridge Yields (up to) ¹	3,000-page High Yield Cartridge, 6,000-page Extra High Yield Cartridge, 1,200-page Cartridge		
Imaging Unit Estimated Yield: Up to	12000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage		
Cartridge(s) Shipping with Product ¹	700-page Black Return Program Toner Cartridges		
Paper Handling			
Included Paper Handling	250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed		
Paper Input Capacity: Up to	Standard: 251 pages 20 lb or 75 gsm bond / Maximum: 251 pages 20 lb or 75 gsm bond		
Paper Output Capacity: Up to	Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond		
Media Types Supported	Card Stock, Envelopes, Paper Labels, Plain Paper, Refer to the Paper & Specialty Media Guide		
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6		
General Information ⁴			
Standard Ports	Ethernet 10/100BaseTX (RJ-45), USB 2.0 Specification Hi-Speed Certified (Type B), 802.11b/g/n Wireless		
Noise Level: Operating	Print: 52 dBA / Copy: 55 dBA / Scan: 52 dBA		
Specified Operating Environment	Humidity: 15 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Meters (9,500 Feet)		
Limited Warranty - See Statement of Limited Warranty	1-Year Advanced Exchange, 3-5 Business Day Ground Shipment		
Size (in. - H x W x D) / Weight (lb.)	13.9 x 16.4 x 14.2 in. / 22 lb.		

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹Average standard page yield value declared in accordance with ISO/IEC 19752. ²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ⁵Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁷Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

© 2019 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. ENERGY STAR® is a U.S. registered mark. Google Cloud Print™ is a trademark of Google, Inc. MOPRIA®, the Mopria®Logo™ and the Mopria®Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

