Lexmark FoIP Solution Readiness Checklist

The Lexmark Fax over IP (FoIP) Solution is a great way for organizations to simplify their fax infrastructure. In order to ensure a smooth installation, the following prerequisites should be met before obtaining the Lexmark FoIP Solution.

- Verify that your Voice over IP (VoIP) phone system supports T.38 faxing.
    - Some VoIP systems support fax but not T.38. Make sure that your VoIP phone system fully supports T.38.
- Verify that your VoIP phone system supports SIP or H.323.
    - The Lexmark FoIP Solution uses SIP or H.323. Therefore, your VoIP phone system must support at least one of them.
- Someone who is knowledgeable about your VoIP phone system should be available to help deploy the solution. This person should have a good understanding of how to configure trunks or endpoints in SIP or H.323, how to turn on T.38 faxing, and how to set up dial plans and call routing.
- Read and be familiar with the Lexmark Fax over IP Solution white paper.
- Determine how you will connect the Lexmark MFP with the FoIP solution:
    - SIP Endpoint with registration
    - SIP Endpoint without registration
    - H.323 Endpoint
    - SIP Trunk with registration
    - SIP Trunk without registration
    - H.323 Trunk
- You must have a way to capture network packets that stream to and from the MFP for troubleshooting and debugging purposes. See the Capture Wireshark Trace Summary document for more information.