Lexmark CS531, CS632, CX532, and CX635 color laser printer and MFP

Announcing Lexmark's new CS531dw, CS632dwe, CX532adwe, and CX635adwe color laser printer and MFP

April 25, 2023

Lexmark

Lexmark announces new CS531, CS632, CX532, and CX635 color laser printer and MFP

Lexmark announces the CS531, CS632, CX532, and CX635 color laser printer and MFP

Description	Part Number	UPC	MSRP
US Pricing			
CS531dw	50M0020	7-34646-73127-0	$863.30
CS632dwe	50M0060	7-34646-73131-7	$1,015.87
CX532adwe	50M7040	7-34646-73128-7	$1,333.73
CX635adwe	50M7080	7-34646-73132-4	$2,160.16
Canada Pricing			
CS531dw	50M0020	7-34646-73127-0	$1,013.95
CS632dwe	50M0060	7-34646-73131-7	$1,193.09
CX532adwe	50M7040	7-34646-73128-7	$1,431.95
CX635adwe	50M7080	7-34646-73132-4	$2,148.52

General Program Information

Key highlights:

I. SFP

Devices	CX532adwe	CX635adwe
Functions	Print / Scan / Copy / anFax	Print / Scan / Copy / anFax
Controller		
FW Architecture	Moja / Claiborne+	Moja / Claiborne+
eSF Capable	Yes	Yes
Processor / Asic	Granite 2	Granite 2
Processor Speed	1.2 GHz	1.2 GHz
Processor Core	Quad Core	Quad Core
Memory Dram - Standard	2 GB DDR4	2 GB DDR4
Memory Dram - Max	2 GB DDR4	2 GB DDR4
Intelligent Storage Drive (ISD)	Optional	Optional
Hard Disk	Optional	Optional
Fax ports	1 analog or via ethernet	1 analog or via ethernet
USB Type-B Device Port - Rear	Yes	Yes
USB Type-A Host Port - Rear	Yes	Yes
USB Type-A Host Port - Front	Yes	Yes
Ethernet port - Rear (10/100)	No	No
Ethernet port - Rear (10/100/1000)	Yes	Yes

Wireless Technology	Standard	Standard
Wireless Channels	802.11b/g/n/ac + BLE	802.11b/g/n/ac + BLE
Op Panel Size	4.3	7
Supplies		
SWE - K (Enterprise)	3K	3K
SWE - CMY (Enterprise)	2K	2K
Max AM - K (Enterprise)	15.8k	20k
Max AM - CMY (Enterprise)	8.8k	11.7k
Black Imaging Kit	150K	150K
Fuser Life	150K	150K
Speeds		
Simplex Letter Tray 1 (up to PPM)	35	42
Simplex A4 Tray 1 (up to PPM)	33	40
Time to First Print (Claim)	7.1	6.5
Time from Ready Mode		
Mono (sec)		
Time to First Print (Claim)	7.6	6.7
Time from Ready Mode		
Color (sec)		
Time to First Print (Claim)	11.6	11.1
Time from Sleep Mode		
Mono (sec)		
Time to First Print (Claim)	11.9	11.3
Time from Sleep Mode		
Color (sec)		
Scan - Simplex Letter Tray 1 (up to PPM)	N/A	N/A
Scan - Simplex A4 Tray 1 (up to PPM)	N/A	N/A
Paper I/O		
Input Capacity std	250	250
Input Capacity max	2001	2001
Output Cap. std	170	170
Output Cap. max	170	170
MPF Input	NA	NA
Print		
Print Resolution (Default)	4800 Color Quality	4800 Color Quality
Print Resolution (Max)	1200x1200	1200x1200
General		
Recommended Monthly Page Volume	1.5-10K	1.5-10K
Max Duty Cycle	100K	125K

Lexmark

II. MFP

Device	CX532adwe	CX635adwe
Functions	Print / Scan / Copy / anFax	Print / Scan / Copy / anFax
Controller		
FW Architecture	Moja / Claiborne+	Moja / Claiborne+
eSF Capable	Yes	Yes
Processor / Asic	Granite 2	Granite 2
Processor Speed	1.2 GHz	1.2 GHz
Processor Core	Quad Core	Quad Core
Memory Dram - Standard	2 GB DDR4	2 GB DDR4
Memory Dram - Max	2 GB DDR4	2 GB DDR4
Intelligent Storage Drive (ISD)	Optional	Optional
Hard Disk	Optional (USB)	Optional (USB)
Fax ports	1 analog or via ethernet	1 analog or via ethernet
USB Type-B Device Port - Rear	Yes	Yes
USB Type-A Host Port - Rear	Yes	Yes
USB Type-A Host Port - Front	Yes	Yes
Ethernet port - Rear (10/100)	No	No
Ethernet port - Rear (10/100/1000)	Yes	Yes
Wireless Technology	Standard	Standard
	Ironman	Ironman
	(except TAA – No wireless)	(except TAA – No wireless)
Wireless Channels	802.11b/g/n/ac + BLE	802.11b/g/n/ac + BLE
Op Panel Size	4.3	7
Supplies		
SWE - K (Enterprise)	3K	3K
SWE - CMY (Enterprise)	2K	2K
Max AM - K (Enterprise)	15.8k	20k
Max AM - CMY (Enterprise)	8.8k	11.7k
Black Imaging Kit	150K	150K
Fuser Life	150K	150K
Speeds		
Simplex Letter Tray 1 (up to PPM)	35	42
Simplex A4 Tray 1 (up to PPM)	33	40
Time to First Print (Claim)	7.2	6.3
Time from Ready Mode Mono (sec)		
Time to First Print (Claim)	11.5	11.4
Time from Sleep Mode Mono		
(sec)		

Scan - Simplex Letter Tray 1 (up to PPM)	52	52
Scan - Simplex A4 Tray 1 (up to PPM)	49	49
Paper I/O		
Input Capacity std	250	250
Input Capacity max	2001	2001
Output Cap. std	200	200
Output Cap. Max	200	200
MPF Input	NA	NA
Print		
Print Resolution (Default)	4800 Color Quality	4800 Color Quality
Print Resolution (Max)	1200x1200	1200x1200
Scan		
Flatbed Size	Legal	Legal
Automatic Document Feeder	DADF	DADF
Scan Resolution (Default)	300x600	300x600
Scan Resolution (Max)	600x600	600x600
Imaging Technology	CIS	CIS
ADF Input Capacity (20 lb sheets)	100	100
ADF Output Capacity (20 lb sheets)	100	100
Multifeed Detection	No	No
OCR	Optional	Optional
Fax Function		
Device-based Fax -Analog modem	YES	YES
Fax over IP (FoIP)	YES, as a Lexmark Licensed Feature	YES, as a Lexmark Licensed Feature
etherFAX (https)	YES	YES
Native Fax Server (SMTP)	YES	YES
Integrated Fax Server (eSF App)	YES, as a Lexmark Licensed Feature	YES, as a Lexmark Licensed Feature
General		
Recommended Monthly Page Volume	1.5-10K	1.5-10K
Max Duty Cycle	100K	125K

Accessibility Features

These products contain enhancements that advance the accessibility of these products, including:

- Users can navigate by swipe and receive voice guidance in a number of languages for navigation and error notification. (Support may require upgrade to latest firmware).

- New touch screen gestures for initiating Voice Guidance and adjusting volume allow users to control device functionality without the need for physical buttons and keys on the control panel.
- Headphone jacks provide private listening on both the single function and multifunction models.
- An optional keyboard can be attached via USB port, providing alternate methods for operating the devices.

In addition, these products will continue to support the Lexmark Accessibility Solution (LAS). This optional application may be installed on MFPs, enabling users to use a web browser at their workstation or mobile device to create a job ticket using their existing assistive technology such as a screen reader, screen magnifier, or voice recognition software. Once the job is submitted to the MFP, the user enters the number on the home screen using the keypad. This can reduce time spent at the MFP specifying job parameters or entering metadata.

Lexmark will make available evaluations of the products according to US Section 508 regulations, European Standard EN 301 549, and the Web Content Accessibility Guidelines (WCAG 2.1).

Please visit the URLs below for more information regarding Lexmark accessibility features.

https://www.lexmark.com/en_us/solutions/print-solutions/accessibility-at-lexmark.html
https://www.lexmark.com/en_us/solutions/government/accessibility-compliance.html

Country of Origin

Description	Country of Origin
Printers and Multifunction Products	PRC, Mexico
Toner Cartridges	PRC, Poland, Juarez
Imaging Unit	PRC
550-Sheet Tray	PRC
Adjustable stand	USA / PRC
Convenience Stapler	PRC

ECCN and HTS numbers

- ECCN Export number = **EAR99**
- HTS Import/Export number = 8443.32.1010 - SFP
  8443.31.0000 - MFP
  8443.99.5015 – Trays, Adjustable Stand, Stapler

Lexmark Security

Please visit https://www.lexmark.com/en_us/solutions/secure-by-design.html for more information.

Firmware Highlights

Firmware Functions

This product incorporates the newest generation of Lexmark firmware known as Claiborne. The following is a high-level summary of enhancements/new functions:

- FW Update from Panel - previously this was EWS only
- Added instructions for cleaning dirty scanner glass
- Support for Cartridge Two-Factor Authentication
- Add a setting to choose not to send the PDF attachment in a fax transmission
- JavaScript Library update
- Move scan data to utilize TLS – (customer transparent security-related initiative)
- Add 'Test email' button in EWS
- Buffered email (Scan and Hold)

Technical Information

Performance

Time to Ready

Device	CS531dw	CS632dwe	CX532adwe	CX635adwe
Time to Ready: Hibernate or Power Off -->Ready	Approximately 65	Approximately 110	Approximately 65	Approximately 65

Note: Time to ready is measured on products at room temperature (22˚ Celsius) and using the factory default settings. This time can be affected by options installed such as RAM, eSF applications, paper handling options, etc., and by changes to default settings.

Time to First Print

Time to First Page (TTFP) is defined from when the job is sent (across USB) until the trailing edge of the first Letter page exits into the standard bin. TTFP is measured using a moderate coverage text page

Device	CS531dw	CS632dwe	CX532adwe	CX635adwe
Time from Ready Mode Mono (sec)	7.1	6.5	7.2	6.3
Time from Ready Mode Color (sec)	7.6	6.7	7.5	6.3
Time from Sleep Mode Mono (sec)	11.6	11.1	11.5	11.4
Time from Sleep Mode Color (sec)	11.9	11.3	11.8	11
Duplex Time from Ready Mode (sec)	13	11.6	12.7	10.8

Scan Feature

- Mono Scan Output: Supports up to 600x600
- Color Scan Output: Supports up to 600x600
- USB and Network TWAIN Drivers
  -For supported operating systems, see Section 8.2.1.

- Scan Destinations:
  - USB Thumbdrive
  - E-mail
  - FTP
  - LDSS
  - Network or USB connected computer
  - Window network folder (requires installation of embedded scan to folder application)

- Supported Compressions:
  - PDF – 1 bit – JBIG2, CCIT G4, Flate
    - 8/24 bit – Flate, JPEG, MRC (mixed raster content requires Hard disk or ISD to be installed)
  - TIFF – 1 bit – CCITT G4
    - 8/24 bit – Packbits, LZW
  - JPG – 8/24 bit – JPEG

- Scan Formats
  - Tiff - Standalone Jobs, not on Host-based jobs
  - JBIG - Standalone Jobs, not on Host-based jobs

  - Jpeg - Both Standalone and Host-based jobs
  - BMP - Both Standalone and Host-based jobs
  - Non-Searchable PDF - Both Standalone and Host-based jobs

  - Searchable PDF - Host-based jobs
  - RTF - Host-based jobs.

- OCR (optional - requires ISD or HDD option and purchase of OCR license)

Fax Specific

The CX532adwe and CX623adwe are with built-in FAX capability. Fax Transmission Speed is < 3 seconds per page.

Copy Speed

Device	CX532adwe	CX635adwe
Simplex Letter Tray 1 (up to PPM)	35	42
Duplex Letter Tray 1 (up to SPM)	17.5	21

Time to First Copy

Device	CX532adwe	CX635adwe
	As fast as	As fast as
ADF Text/Photo Letter Standby/Ready Mono (sec)	7.6	6.6
ADF Text/Photo Letter Standby/Ready Color (sec)	7.6	6.5

Copy Features

Copy Resolution
Up to 600 x 600 dpi
Maximum Number of Copies
9999

The following options are available from the scan menu

- Copy From Size
- Copy to size
- Scale
  - 25% to 400%
- Darkness
- Duplex
- Collate
- Content
  - Text, Text/Photo, Photo, Graphics
- Save As Shortcut

Environmental Specifications

Temperature and Humidity

These products are designed to operate in the following environmental conditions. Certain media used such as envelopes or labels may require a more restricted environment.

Environment	Specifications
Operating Temperature and Relative Humidity	10 to 32.2°C (50 to 90°F) and 15 to 80% RH 15.6 to 32.2°C (60 to 90°F) and 8 to 80% RH Maximum wet-bulb temperature (2): 22.8°C (73°F) Non-condensing environment
Operating Altitude	0 - 2900m (0 - 9500 ft.)
Printer / Cartridge / IU Long-Term Storage (1)	15.6 to 32.2°C (60 to 90°F) and 8 to 80% RH Maximum wet-bulb temperature2: 22.8°C (73°F)
Printer / Cartridge / IU Short-Term Shipping	-40 to 40°C (-40 to 104°F)

Power & Electrical Specifications

Device	CS531dw	CS632dwe	CX532adwe	CX635adwe
Off (W)	0.2	0.2	0.2	0.2
Hibernate (W)	0.2	0.2	0.2	0.2
Sleep State (W)	1	1	1.3	1.3
Ready Low Power State - Tier 2 (W)	20.8	21.3	25.5	29
Simplex Printing (W)	514	574	574	587
Duplex Printing (W)	362	383	383	402
Typical Electricity Consumption (kWh/wk) Default Mode	0.46	0.52	0.51	0.57

Media Input and Output Support

Input/Output Configurations and Capacities

Configuration and Capacities	CS737dze	CX737adzse
Number of Standard Sources	2	2
Maximum Number of optional trays	4	4
Maximum Number of Input Sources	6	6
Standard Trays	550	550
Manual Slot	No	No
Multipurpose Tray Capacity	100	100
Total Standard Capacity	650	650
Maximum Input Capacity	2850	2850
Standard Output Bin Capacity (printer top)	300	300
Maximum Output Capacity	300	300
Standard Internal Duplex Print	Yes	Yes

For more information regarding media size and support, please visit the Paper and Specialty Guide link below.

Paper and Specialty Media Guide

Supplies and Options

Supplies

Supplies are designed for use only with this line of printer and multifunction product models.

NOTE: *All SWE (ship with equipment) cartridges are shipped under the Lexmark Return Program license agreement.*

Enterprise		CS531dw	CS632dwe	CX532adwe	CX635adwe
K Toner	SWE	3K	3K	3K	3K
	Toner Cartridge	3K	3K	3K	3K
	High Yield Toner Cartridge	15.8k	20k	15.8k	20k
C / M / Y Toner	SWE	2K	2K	2K	2K
	Toner Cartridge	2K	2K	2K	2K
	High Yield Toner Cartridge	8.8k	11.7k	8.8k	11.7k

Other Supplies

Supply Item	All Models
Imaging Unit - Mono	150K
Imaging Unit - Color	150K

Photoconductor - Mono	N/A
Photoconductor - Color	N/A
Waste Toner Bottle	30K

Input, Output & Other Media Options

General Compatibility

All models in this family use the same input trays. The input Trays are not compatible with the predecessor product family.

650-Sheet Duo Tray (Includes 550-sheet Tray and 100-sheet Multipurpose Tray) – This optional input source installs beneath the printer as the first optional tray. All models support a single Duo tray and up to two optional 550-sheet trays.

550-Sheet Tray – This optional input source installs beneath the printer. It holds approximately 550 sheets of (20 lb.) paper. Multiple optional Trays are supported simultaneously.

The authoritative tables of maximum Printer/MFP/Paper Options/Furniture combinations is publicly available at www.lexmark.com/multifunctionprinters Please refer to this information before purchasing any additional paper input options.

Electronic Options

Intelligent Storage Drive (ISD)

This solid-state storage card will replace the hard drive for most customers. It comes with 120 GB of storage space which can be used for disk and/or user flash purposes, as well as most DBCS fonts (Simplified Chinese, Traditional Chinese, Japanese, Korean and Arabic). Hebrew is available through distribution in Israel. This solution card will come standard on some MFP models in the Lexmark line (models with the “s” suffix beginning with the CX73x series). For other electronic options, see Options section.

Bar Code Support

Bar Code engine and bar code font support is available through an electronic license to activate the function. Use of the ISD is recommended for additional storage, depending on the customer application.

IPDS Support

IPDS support is available through an electronic license to activate the function. The Lexmark IPDS solution provides configuration flexibility and compatibility for AFP/IPDS printing on TCP/IP LAN printers. It is compatible with IBMTM System z (mainframe) or IBM iSeries (AS/400TM) applications that output AFP/IPDS data stream through the Print Services Facility (PSF).

Connectivity and Compatibility

Built in Connectivity

These devices ship with 10/100/1000 Base TX Ethernet onboard the controller card and a USB-B 2.0 High-speed device port in back of the printer. They also include (1) USB-A 2.0 High-Speed host port on the front of the device and (1) USB-A 2.0 High-Speed host port on the back of the device.

Operating System and Software Compatibility

Operation System		
Windows	Windows XP, XP x64, Vista, Vista x64, 7, 7 x64, 8, 8 x64, 8.1, 8.1 x64, 10, 10 x64	
	Windows Server 2008, 2012, 2012 R2	
Apple	Support is provided through AirPrint and AirScan only	
Novell Operating System	Novell NetWare 6.5 Open Enterprise Server 3	
	Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3	
	Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)	
	Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64)	
	Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)	
Linux OS	Ubuntu 18.04 LTS	SUSE Linux Enterprise Server 15 SP2
	Ubuntu 20.04	Red Hat Linux 7.9
	Debian 10	Red Hat Linux 8.3
	Debian 9.4	OpenSUSE 15.1
	Fedora 32	OpenSUSE 15.2
	Fedora 33	
	SUSE Linux Enterprise Server 12 SP5	

AirPrint

All models are AirPrint enabled. AirPrint enables wireless printing from select Apple products without installing print drivers or configuring the print queue.

Mopria

All models are Mopria certified. The Mopria Alliance is a non-profit membership organization of leading global technology companies with the goal of providing simple wireless printing from smartphones, tablets and other mobile devices.

Software Solutions

eSF Based solutions

These products include the Lexmark Embedded Solutions Framework (sSF) in the firmware. This capability enables eSF based solutions to be installed and run on the device. Note that some eSF applications inherently require an installed storage drive to function.

Remote op panel is included in the base firmware of all eTask products.

These apps are preloaded on devices with 4.3” panels (CS531, CS632, CX532, C2335, XC2335):

- Display Customization

These apps are preloaded on devices with 7” panels (CX635):

- Scan Center
- Display Customization
- Shortcut Center
- Card Copy

Other Lexmark solutions are available to complement this product family. For more information, contact your Sales Rep.

Supported Configurations / Furniture

Note: The authoritative tables of maximum Printer/MFP/furniture combinations are publicly available at

http://www.lexmark.com/publications/furniture_safety/

Packaging & Shipping Information

Packaged Printers				
Enterprise	CS531dw	CS632dwe	CX532adwe	CX635adwe
Height (in)	15.8	15.8	23.6	23.6
Height (mm)	402	402	600	600
Length (in)	23.4	23.4	25	25
Length (mm)	595	595	636	636
Width (in)	19.5	19.5	22.6	22.6
Width (mm)	495	495	575	575
Weight (lb)	52.5	52.5	71	71
Weight (kg)	23.9	23.9	32.3	32.3

Packaged Options			
	650 Sheet Duo Tray	**550 Sheet Tray**	**Convenience Stapler**
Height (in)	18.8	18.8	4.4
Height (mm)	478	478	112
Length (in)	20	20	10.8
Length (mm)	508	508	275
Width (in)	8.6	8.6	9.8
Width (mm)	218	218	250
Weight (lb)	11.5	11.5	2.4
Weight (kg)	5.2	5.2	1.1

Toner Cartridges & Imaging Unit

Individual Carton Specifications					
Unit of Measure		**Length**	**Width**	**Height**	**Weight**
Imaging Kits					
Black Return Program	in/lb	21.46	15.08	12.6	7.125
	mm/kg	545	383	323	3.232
Black & Color (CMYK) Return Program	in/lb	21.46	15.08	12.6	11.074
	mm/kg	545	383	323	5.023
Developer Units					
Cyan	in/lb	19.29	5.87	6.46	2.352
	mm/kg	490	149	164	1.067
Magenta	in/lb	19.29	5.87	6.46	2.352
	mm/kg	490	149	164	1.067
Yellow	in/lb	19.29	5.87	6.46	2.352
	mm/kg	490	149	164	1.067
Black	in/lb	19.29	5.87	6.46	2.352
	mm/kg	490	149	164	1.067
Waste Toner Bottle					
	in/lb	18.307	7.559	5.512	1.649
	mm/kg	465	192	140	0.748

For more details regarding supplies packaging and specs, see separate announcement letters for supplies.

Toners – Case Quantities & Pallet

Shipping Dimensions							
Unit of Measure			**Carton Qty**	**Length**	**Width**	**Height**	**Weight**
2K Cyan	in/lb	Pallet	480	47.992	40	42.559	407.229
	mm/kg			1219	1016	1081	184.716
2K Magenta	in/lb	Pallet	480	47.992	40	42.559	401.938
	mm/kg			1219	1016	1081	182.316
2K Yellow	in/lb	Pallet	480	47.992	40	42.559	399.822
	mm/kg			1219	1016	1081	181.356
3K Black	in/lb	Pallet	480	47.992	40	42.559	415.695
	mm/kg			1219	1016	1081	188.556
8.8K Cyan	in/lb	Pallet	480	47.992	40	42.559	499.294

	mm/kg			1219	1016	1081	226.476
8.8K Magenta	in/lb	Pallet	480	47.992	40	42.559	490.828
	mm/kg			1219	1016	1081	222.636
8.8K Yellow	in/lb	Pallet	480	47.992	40	42.559	488.712
	mm/kg			1219	1016	1081	221.676
11.7K Cyan	in/lb	Pallet	480	47.992	40	42.559	536.332
	mm/kg			1219	1016	1081	243.276
11.7K Magenta	in/lb	Pallet	480	47.992	40	42.559	536.332
	mm/kg			1219	1016	1081	243.276
11.7K Yellow	in/lb	Pallet	480	47.992	40	42.559	536.332
	mm/kg			1219	1016	1081	243.276
15.8 K Black	in/lb	Pallet	480	47.992	40	42.559	583.952
	mm/kg			1219	1016	1081	264.876
20K Black	in/lb	Pallet	480	47.992	40	42.559	665.434
	mm/kg			1219	1016	1081	301.836

For more details regarding supplies packaging and specs, see separate announcement letters for supplies.

Physical Dimensions

Enterprise	CS531dw	CS632dwe	CX532adwe	CX635adwe
Height (in)	12.5	12.5	19.3	19.3
Height (mm)	318.3	318.3	491.4	491.4
Length (in)	17.9	17.9	18.9	18.9
Length (mm)	455	455	479	479
Width (in)	16.6	16.6	18.7	18.7
Width (mm)	422.5	422.5	475.1	475.1
Weight (lb)	45.31	45.31	59.5	59.5
Weight (kg)	20.55	20.55	27.1	27.1

Ordering Information

Printers and MFPs

Marketing Name	Voltage	TLI	UPC Code
CS531dw	LV	50M0020	7-34646-73127-0
CS632dwe	LV	50M0060	7-34646-73131-7
CX532adwe	LV	50M7040	7-34646-73128-7
CX635adwe	LV	50M7080	7-34646-73132-4

Lexmark

Options and Features

TLI	UPC Code	Description	Compatibility
Paper Handling			
50M7550	7-34646-73727-2	550-Sheet Tray	All Models
50M7650	7-34646-73728-9	650-Sheet Duo Tray	All Models
47C4500	7-34646-72710-5	Convenience Stapler Americas LV	CX532, CX635,
47C4590	7-34646-72711-2	Convenience Stapler EMEA + Nordics + Switzerland HV	CX532, CX635,
47C4595	7-34646-73852-1	Convenience Stapler Israel HV	CX532, CX635,
47C4596	7-34646-73849-1	Convenience Stapler ES Africa HV	CX532, CX635,
47C4593	7-34646-73850-7	Convenience Stapler UK HV	CX532, CX635,
47C4597	7-34646-73846-0	Convenience Stapler ANZ HV	CX532, CX635,
Furniture			
40C2300	7-34646-60548-9	Adjustable Printer Stand	All Models
3073173	7-34646-43754-7	Swivel Cabinet	All Models
Keyboard			
57X7040	7-34646-57531-7	Keyboard - English	CS632, CX532, CX635,
Security			
Trusted Platform Module (TPM)			Standard on all models except for PNs sold into import-restricted countries.
Authentication Devices			
57X0300	7-34646-61694-2	Contact Front Solutions Module	CS531, CS632, CX532, CX635, C2335
57X0301	7-34646-61693-5	Contactless Front Solutions Module	CS531, CS632, CX532, CX635, ,
Note: Card Authentication and other solutions (including card reader drivers) are sold separately.			

TLI	UPC Code	Description	Compatibility
Storage Devices			
57X9528	7-34646-72793-8	Intelligent Storage Device (ISD) – Bulk Storage + User Flash(2GB)	CS531, CS632, CX532, CX635, C2335, XC2335
27X0805	7-34646-68939-7	500GB+ USB Hard Disk Drive (Backpack)	CS632, CX532, CX635, XC2335
Wireless			
802.11ac 5GHz Dual Band Wireless with Bluetooth 5.0			Standard on all models except for TAA PNs
Local / Network Interface Cards			
27X0800	7-34646-63484-7	RS-232C Serial Interface Card (ISP Backpack Kit)	All models – via SPR only
27X0801	7-34646-63885-2	Parallel 1284-B Interface Card Kit (ISP Backpack Kit)	All models – via SPR only
27X0812	7-34646-63946-0	MarkNet N8230 Fiber Ethernet 100BASE-FX(LC), 1000BASE-SX(LC)	All models – via SPR only

		- Thin Fiber Interface Card* (ISP Backpack Kit)	
Miscellaneous			
1021294	7-34646-06513-9	2-meter USB Printer Cable	All
SPD0001	7-34646-57177-7	Surge Protection Device LV	All
SPD0002	7-34646-57187-6	Surge Protection Device HV	All

Supplies

Part #	UPC Code	Yld	Description	Compatibility
Return Program Imaging Kits (All Regions)				
75M0ZK0	7-34646-74143-9	150	Black Return Program Imaging Kit	All models
75M0ZV0	7-34646-74144-6	150	Black and Color Return Program Imaging Kit	All models
Non-Return Program Imaging Kits (All Regions)				
75M0Z10	7-34646-74145-3	150	Black Imaging Kit	All models
75M0Z50	7-34646-74146-0	150	Black and Color Imaging Kit	All models
Waste Toner Bottle				
75M0W00	7-34646-74147-7	30	Waste Toner Bottle	All models
Staple Cartridges				
35S8500	7-34646-44341-8	1000 staples	Lexmark Staple Cartridge Refill (5-pack)	Convenience Stapler (all part numbers)

Part #	UPC Code	Yld	Description	Compatibility
75M10C0	7-34646-74160-6	2	Cyan Return Program Toner Cartridge	CS531, CS632, CX532, CX635
75M10M0	7-34646-74163-6	2	Magenta Return Program Toner Cartridge	CS531, CS632, CX532, CX635
75M10Y0	7-34646-74162-0	2	Yellow Return Program Toner Cartridge	CS531, CS632, CX532, CX635
75M10K0	7-34646-74163-7	3	Black Return Program Toner Cartridge	CS531, CS632, CX532, CX635
75M1HC0	7-34646-74164-4	8.8	Cyan High Yield Return Program Toner Cartridge	CS531, CX532
75M1HM0	7-34646-74165-5	8.8	Magenta High Yield Return Program Toner Cartridge	CS531, CX532
75M1HY0	7-34646-74200-9	8.8	Yellow High Yield Return Program Toner Cartridge	CS531, CX532
75M1HK0	7-34646-74166-8	15.8	Black High Yield Return Program Toner Cartridge	CS531, CX532
75M1XC0	7-34646-74167-5	11.7	Cyan Extra High Yield Return Program Toner Cartridge	CS632, CX635
75M1XM0	7-34646-74168-2	11.7	Magenta Extra High Yield Return Program Toner Cartridge	CS632, CX635
75M1XY0	7-34646-74169-9	11.7	Yellow Extra High Yield Return Program Toner Cartridge	CS632, CX635
75M1XK0	7-34646-74170-5	20	Black Extra High Yield Return Program Toner Cartridge	CS632, CX635

For more information, see separate announcement letters for supplies.

Package Contents & Publications

Contents may vary by country. Generally, the printer product package includes the items listed in the table below:

North America
Printer or MFP
3.0K Black/2.0K Color Return Program SWE Cartridges
Black and Color Return Program Imaging Kit
Power Cord(s) – Country Dependent
Wordless Setup Sheet (Network and Local Attachment)
NEW QR Code Setup Sheet (no CD)
Safety Information Sheet
Safety Stability Sheet
Warranty Information (Country Dependent)

A Product Information Guide which contains basic safety, environmental, and regulatory information for his product is provided on the Software and Documentation CD. An Information center, User's Guide, product how-to videos, and other user documentation is available at http://support.lexmark.com.

Customer Responsibilities and Installation

This family of products is designed for customer setup. The Setup instructions shipped with the device contain all instructions needed for setting up the device. The CD included with each device provides installation utilities and drivers as well as the Product Information Guide. The Technical Reference is available from the Lexmark Web Site. A link for web-based device registration is provided on the Software and Documentation CD. A power cord is provided with the device.

Problem Determination

The installation procedure outlined in the Setup Sheet includes a self-test power-up for verification of proper setup. Should an error occur during the setup, the troubleshooting section contained on Lexmark.com will assist the customer in identifying the appropriate corrective action.

Warranty and Service

See Statement of Limited Warranty for details

Warranty Terms

One Year Onsite Parts and Labor Warranty will be offered worldwide on these models.

	US	Canada
Warranty Period	1 year	1 year
Base Warranty Service Delivery Type	AE for SFP OSR for MFP	AE for SFP OSR for MFP

Legend:
AE = Advance Exchange
OSR = Onsite Repair Service response
NBD = Next Business Day

Service Parts

Recommended service parts may be ordered from Lexmark.com. Lexmark Authorized Service Provider may find ordering procedures and terms on the Lexmark Authorized Service Provider web page.

Maintenance Kits

All fusers and maintenance kit fusers are Field Replaceable Units (FRUs). A trained Service Technician is required to replace.

The ADF maintenance kit, integrated, and optional paper tray pick roller are CRUs. No tools are needed to replace. The integrated and optional paper tray pick roller have a common CRU.

At rated life the following items will need to be replaced as part of a maintenance interval. Life of each service consumable is listed in the table below.

Fuser maintenance kit (fuser, media pick roller)
ADF maintenance kit (pick roller, separator bracket)

Note that it is important to install the correct voltage Fuser Maintenance Kit for the type of fuser that is installed in the printer.

Administrative Information

Trademark and Copyright Notices

© 2023 Lexmark International, Inc. All rights reserved.

Lexmark and the Lexmark logo are trademarks or registered trademarks of Lexmark International, Inc. or its subsidiaries in the United States and/or other countries. All other trademarks are the property of their respective owners.

Information contained in this document is subject to change without notice.