SENSING & SWITCHING SOLUTIONS FOR GAS/FUEL PUMPS

Application Brief



Honeywell



Honeywell solutions play an indispensable role in the rigorous demands of modern gas/fuel pump systems, where every actuation must be precise, consistent, and fail-safe.

BACKGROUND

In a fuel dispenser, switches are tasked with critical responsibilities: detecting nozzle lift and position, safeguards for emergency shutoff, interlocking with metering electronics, and enabling accurate calibration feedback. These functions demand switches that deliver exceptional repeatability — consistently tripping at precise actuator positions — and long-term stability, as misfires or mechanical drift could result in measurement inaccuracies (typically within ±0.3 %) or unsafe fueling conditions. Furthermore, dispensers operate in harsh environments — exposed to fuel vapors, temperature extremes, dust, and vibration — so switches must also provide durable sealing, explosion safety ratings, and lifecycle reliability measured in millions of cycles. Integrating high-performance solutions ensures that fuel pumps not only comply with stringent calibration and safety standards (e.g., NIST, EPA, ATEX/IECEx), but also uphold uptime, minimize maintenance interventions, and instill consumer trust through accuracy and resilience.

Honeywell switches and sensors can be deployed throughout gas/fuel pump systems. Here are a few examples of their use and the critical task(s) they perform.

SENSORS & SWITCHES FOR GAS PUMP APPLICATIONS



FUEL DISPENSING CONTROL

In fuel dispensers, electromechanical switches provide the deterministic response necessary for precise metering — actuating exactly at set thresholds to ensure accurate fuel flow measurement and repeatability.


Nozzle State Detection and Activation

Electromechanical switches are pivotal in initiating and stopping the fueling process by accurately detecting the state of the nozzle — whether it is lifted from its holster, inserted into a vehicle's tank, or returned to its rest position. When a user lifts the refueling nozzle, the fuel dispenser automatically begins the refueling process; when the nozzle is returned, the process stops. This seemingly simple action is underpinned by a complex detection and control system, where the "lift switch" is a key component. There are two solution types commonly used for this function.



MICRO SWITCH BZ Large Basic Switch

Basic Switches – These mechanical switches have a relatively straightforward working principle. When the refueling gun is lifted, a lever or button of the basic switch is pressed, closing a circuit and signaling the refueling machine to start. Conversely, when the refueling nozzle is replaced, the circuit opens, stopping the process. Basic switches are valued for their ease of use, simple design, low cost, and quick response, providing an almost instantaneous signal to begin refueling. Honeywell basic switches' ruggedness and sealing (IP67) are better able to withstand environmental pollutants like dust and moisture in outdoor gas environments.




MICRO SWITCH V15W Water=tight Basic Switch

Modern fuel dispensers rely on precise nozzle state detection that is designed to provide safe and accurate fuel delivery. The Honeywell **MICRO SWITCH BZ Series Large Basic Switches** are engineered for this critical function, featuring robust snap-action mechanisms and low differential travel that ensure consistent, repeatable actuation — even under mechanical stress. With current ratings up to 25 A and durable designs tested for over 10 million mechanical cycles, BZ switches maintain operational integrity and precision in nozzle presence/absence detection, validating each fueling cycle with confidence.



MICRO SWITCH ZD Subminiature Basic Switch

For environments where fuel dispensers are exposed to harsh conditions — such as temperature extremes, rain, snow, dust, and chemical pollutants — **Sealed Miniature and Subminiature Switches like V15W, ZW, and ZD Series** offer dependable performance. These IP67-rated switches feature sealed plungers and wire leads (V15W) or encapsulated housings (ZW/ZD), protecting critical internal contacts against moisture and contaminants. In nozzle activation, these switches provide rapid, repeatable feedback signals to the dispenser's control logic — confirming nozzle latch/unlatch events with minimal signal noise and superior electrical integrity, even in harsh outdoor installations.



MICRO SWITCH ZW Subminiature Basic Switch

Beyond sealed miniature options, Honeywell delivers tailored solutions for every region of the dispenser. Large BZ switches serve as rugged workhorses at high-current metering interfaces, while V15W elastomer sealed and the compact-yet-tough ZW/ZD switches handle safety interlocks, emergency shut off, and nozzle position feedback in environmental extremes. All variants are designed to withstand temperature ranges from –55°C to over 100°C, support global electrical standards (UL, cUL, ENEC, CQC), and resist ingress from particulates and fluids — helping fuel dispenser systems meet stringent regulatory requirements and maintain uptime under every weather condition.

Hall-effect Sensors – These non-contact electronic sensors use magnetic field changes for detection. When the refueling nozzle is lifted, the position of a magnet inside the nozzle changes. The Hall-effect sensor detects this magnetic field change, triggering the refueling machine to start. When the nozzle is returned, the magnetic field reverts to its original state, the Hall-effect sensor stops detecting, and the refueling process ends. These sensors offer high precision, high reliability, and fast response speeds, with minimal false triggering.


Honeywell offers several non-contact magnetic (Hall-effect and magnetoresistive) sensors ideal for nozzle-state detection in fuel dispensers, where reliability and environmental robustness are essential.



RTP Hall-effect Rotary Position Sensor

RTY/RTP Series Hall-effect Rotary Position Sensors use a Hall-effect IC with a rotating magnet — typically integrated into the nozzle mount assembly — to sense nozzle lift or rotation. RTY models include a shaft with an internal magnet that rotates with nozzle insertion or removal, converting angular movement into a voltage signal. RTP variants separate the magnet from the sensor body, reducing mechanical wear and increasing longevity. Both are housed in rugged, IP69K-rated packages, making them highly resistant to dust, rain, and pressure washing.

The omnipolar **2SS52M/SS552MT** Series uses advanced AMR technology, offering high sensitivity to both magnet polarities. This enables detection of subtle position shifts in the nozzle magnet (e.g., between seated and lifted states) with extended air-gap tolerances — allowing a durable, sealed design. With SMT packaging and stable performance across wide voltage and temperature ranges, these sensors offer a solid-state, long-life alternative to mechanical switches for nozzle-presence feedback.



2SS52M/SS552MT Omnipolar Magnetic Sensor IC

For minimalist, ultra-low power use cases — like confirming nozzle presence or insertion — Honeywell Nanopower MR family (e.g., **SM351LT, SM353LT**) and linear Hall ICs (**SS39ET/SS49E**) offer compact, efficient solutions. They detect the embedded magnet in the nozzle with low hysteresis and stable temperature characteristics. Although generally not housed as IP-rated assemblies, they excel in PCB-embedded designs protected within the dispenser head.



Nanopower Series Magnetic Sensor IC

Many locations require a two-step activation process for a fuel dispenser due to fire code regulations. This often involves the nozzle state detection (e.g., basic switch or Hall sensor) providing a first signal, followed by a secondary activation means, such as a push button on the dispenser or a credit card reader. This double activation system prevents inadvertent fuel dispensing and enhances safety.

Fuel Flow Regulation

Electromechanical switches contribute to controlling the rate and stopping fuel flow, ensuring efficient and safe dispensing. The nozzle itself incorporates mechanisms for flow control. When the gas pump handle is squeezed, it opens a valve inside the nozzle, initiating fuel flow. Some nozzles feature adjustable flow rate settings and a hold-open clip for hands-free operation, allowing users to tailor fueling speed.

Pressure switches and sensors can monitor the flow of liquid or gas and trigger a signal when a pre-set flow rate is reached, capable of signaling an action like shutting down the flow. While providing continuous measurements, pressure switches and sensors offer a specific trigger point. These switches play a role in ensuring that fuel is dispensed within safe and regulated flow parameters.

Fuel pressure regulators, while primarily valves, are electromechanical in their control aspect. They consist of a spring and diaphragm that open and close as required to return excess fuel to the tank, maintaining consistent fuel pressure in the system. This consistent pressure is crucial for the accurate operation of the flow meters and overall dispensing efficiency. The ability to control pressure to precise levels, sometimes with adjustable regulators and gauges, implies an underlying control loop that may involve pressure switches providing feedback to electronic controls that then actuate these mechanical regulators.

Honeywell offers several mechanical pressure switches and electronic pressure sensors ideal for fuel pump systems — particularly for managing fuel flow regulation, monitoring, and end-of-flow signaling. These devices help with smooth, safe dispensing control by activating or interrupting downstream processes based on precise pressure thresholds.



LE Series Pressure Switch

LP/LE Series Compact Pressure Switches operate within a 3.5 psi to 150 psi range and feature gold contacts, SPDT/SPST configurations, and IP67-rated housings. In fuel dispensers, they can detect pressure drops when a nozzle is lifted or flow stops, triggering pump shutdown or signaling end-of-flow events with dependable snap-action contacts and minimal contact wear. **5000 Series** pressure switches are designed for extended-duty applications. These factory- or field-adjustable switches utilize a Kapton diaphragm compatible with hydrocarbon fuels and come with Metri-Pack connectors for robust sealing. With set points adjustable from 0.5 psi to 150 psi, they are ideal for detecting both low-flow or high-pressure conditions, enhancing operational safety and providing reliable triggers for flow control.



5000 Series Pressure Switch

MLH Series Heavy-Duty, Media-Isolated Pressure Sensors deliver 4 mA to 20 mA output in ranges up to 1000 psi. These two-wire, ASIC-based sensors offer excellent total error band (~2 %FSS), all-metal wetted parts, and IP65-rated enclosures. In dispenser systems, MLH units enable real-time flow-rate monitoring; control systems can interpret pressure levels to regulate pump speed and precisely identify end-of-cycle conditions through pressure decay patterns.




MLH Heavy-Duty Pressure Sensor

These stainless-steel, media-isolated **MIP Series Pressure Sensors** cover 1 bar to 70 bar with analog or digital outputs, full temperature compensation (–40°C to 125°C), and tight error bands (±0.75 %FSS). Ideal for high-pressure fuel applications, MIP sensors provide fast, accurate pressure signals that support dynamic flow control, over-pressure protection, and precise cut-off actions at end-of-fill events.



MIP Heavy-Duty Pressure Sensor



Motor Control

Electromechanical switches are fundamental to controlling the electric motor that drives the fuel pump, whether it's a submersible pump in the tank or a suction pump within the dispenser unit. The motor is essentially the "heart of the system". When the dispenser is activated, the motor drives a gear pump that sucks fuel from the underground storage tank, creating pressure to push fuel through the system to the nozzle. The control of this motor's operation is critical for initiating and stopping fuel delivery.

Motor control disconnect switches are specifically designed for use in harsh industrial applications, ensuring safety, reduced downtime, and code compliance. These heavy-duty switches feature durable lever handles and robust switch mechanisms that can withstand repeated use. They are often housed in NEMA Type 4X or IP69K rated enclosures, providing protection against washdowns, extreme temperatures, chemicals, and corrosive elements, which are common in fuel station environments. These switches allow for the safe isolation of power to the motor for maintenance or in emergency situations, as often gas pumps feature high-visibility red handles that can be padlocked to meet OSHA lockout/tagout requirements.

Honeywell offers rugged MICRO SWITCH limit switches ideal for motor-control disconnects in fuel/gas pump environments. These switches help with safe isolation of pump motors, protect personnel, and comply with regulatory and maintenance protocols.

The **HDLS Series Heavy-Duty Limit Switch** features a robust zinc or stainless-steel housing with modular actuator heads. They carry NEMA 1, 3, 4, 4X, 6, 6P, 12, 13 and IP65/66/67 ratings, making them resistant to washdowns, extreme temperatures, dust, water ingress, and corrosive agents — perfect for the fuel-station environment. Fully potted variants offer epoxy-filled bodies for even greater protection against moisture and contaminants. In motor-control disconnect applications, the HDLS Series can be mounted to isolator switch mechanisms (e.g., rotary disconnect handles). When the gas pump's red, high-visibility lever is turned to the OFF position, the switch's internal snap-action contacts open, breaking the motor circuit. These switches are designed to operate reliably for upwards of 50 million mechanical cycles, supporting frequent shut-downs and emergency lockout/tagout procedures.

For more compact configurations or less frequent actuation points, the **MICRO SWITCH LS Series** delivers IP67 and NEMA 1, 3, 4, 6, 13 protection in a smaller die-cast metal form factor. They provide snap-action switching and modular actuator choices to integrate into pump housings with space. Positive snap-action contacts and high current ratings (e.g., 10 A @ 600 Vac) are designed to provide motor cut-off even under high-load conditions.



MICRO SWITCH HDLS (LSA) Limit Switch



MICRO SWITCH LS Limit Switch

SAFETY AND EMERGENCY SYSTEMS

The inherent hazards of handling flammable liquids necessitate robust safety and emergency systems, many of which rely on electromechanical switches.



MICRO SWITCH E-Stop Switch

Emergency stop (E-Stop) controls are paramount safety features integrated into every fuel dispenser. These easily identifiable buttons, often large and red, are strategically placed to immediately halt fuel flow if problems occur, such as a large spill, fire, or accident.

An emergency stop switch functions through a three-step process:

- **Activation:** When pressed, the E-Stop immediately interrupts the power supply to the machinery, causing an abrupt stop
- **Wiring and Circuitry:** The emergency stop is wired into the control circuit of the equipment, often in series with other safety devices. When activated, it breaks the circuit, preventing power from reaching the pump's motor or other critical components, thereby shutting it down
- **Latching Mechanism:** Most emergency stops have a latching feature, meaning that once pressed, the switch stays in the "off" position until manually reset. Resetting often involves turning the button clockwise, a push-lock turn, or using a separate reset button. This ensures that the fuel supply remains off until the emergency condition is cleared

These switches are crucial for ensuring safety in various industrial and commercial settings, serving as a last line of defense when other safeguards fail. They help prevent potential accidents, injuries, and hazards by swiftly stopping operations.

Honeywell E-Stop (Emergency-Stop) switches are ideal for integration into fuel dispenser systems, along with details on how and why they're suited for this critical safety function:

Honeywell Push-Pull/E-Stop Switches are design with a robust sealed construction. They feature sliding-contact mechanisms protected by dual O-ring seals, providing environmental ratings up to IP67 and proven resistance to moisture, dust, vibration, pressure wash, UV, and chemical exposure. When the large red knob is pulled or pushed, internal dual-circuit contacts instantly open (or close, depending on design), helping with reliable and clean electrical disconnection even under fault conditions. Strategically placed and easy to actuate, the E-Stop knob is designed to halt fuel flow and electrical power to pump motors, preventing further operation in events like spills, fires, or system malfunctions. IP67 sealing combined with UV-resistant, weatherproof knobs (available in red for high visibility) ensure reliable performance in rain, snow, heat, and wash-down environments typical of fuel station operations



MICRO SWITCH GK Key Interlock Safety Switch

Safety Interlocks

Safety interlock systems are employed to ensure safe operation and maintenance by reliably monitoring and protecting protective guards, doors, and covers. These systems ensure that machinery can only operate when these barriers are securely closed, preventing access to hazardous areas during operation.

Key interlock switches are a common type, designed with two parts: a switch mounted on the stationary portion of a structure and an actuator (key) mounted on the movable portion, such as a door or machine guard. The actuation of the interlock switch occurs only when the corresponding key is inserted into its slot, which happens when the door or guard is closed. The special key design makes these switches extremely difficult to defeat, enhancing tamper-proof capabilities. When the door is opened, the key is removed, opening the switch's normally closed contacts and interrupting the machine's control circuit, thereby stopping the machine.



Safety interlock switches are robust and survivable, immune to dirty, greasy, and adverse environmental conditions, and compliant with international safety standards. They often incorporate positive action mechanisms and anti-tamper features to prevent attempts to bypass their safety function.

Honeywell MICRO SWITCH GK Series safety interlock limit switches are designed to enhance safety in fuel and gas pump systems, by ensuring that machinery operates only when protective barriers are securely closed. In fuel or gas pump systems, safety is paramount due to the presence of flammable substances. The GK Series switches serve as a safeguard by monitoring access points like maintenance doors or protective covers.

If the guard or door is opened, the key is removed from the switch, causing the NC contacts to open. This action interrupts the control circuit, immediately halting pump operation to prevent potential hazards. With dual entry positions, the key may be inserted from the top or side, offering flexibility in mounting configurations.


Access Panel/Open Door Locks

In gas pump applications, ensuring safety and preventing unauthorized access are vital to safety and performance. Honeywell BZ and DM/DP Series switches are instrumental in achieving these objectives by monitoring access panels and halting operations if tampering is detected. When integrated into the pump's access panels, these switches detect unauthorized openings or tampering. If an access panel is removed or improperly secured, the switch changes state, triggering the pump's control system to cease fuel dispensing. This immediate response helps prevent potential hazards, such as fuel theft or environmental contamination, ensuring both safety and compliance with regulatory standards.



MICRO SWITCH BZ Large Basic Switch

MICRO SWITCH BZ Series large basic switches are often mounted directly on the pump cabinet frame, close to the hinged edge or latch area of the access panel. When the door is closed, the panel presses the actuator (e.g., plunger or lever) to hold the switch closed.



MICRO SWITCH DM Snap-In Panel-Mount Basic Switch

MICRO SWITCH DP/DM Series low-profile, snap-in switches are ideal for mounting directly into a small cutout in the access panel or frame. They're often positioned near the panel edge so that closing the panel depresses the actuator (momentary, push-pull, or pull-to-cheat) and completes the circuit. The snap-in design allows quick installation without screws, and they feature quick-connect terminals for wiring ease. Their compact nature makes them suitable inside tight spaces or flush with the panel surface.

METERING AND CALIBRATION

Electromechanical components are central to the accurate measurement of fuel and the ongoing calibration processes that ensure transactional integrity.

Pressure Monitoring and Calibration

Pressure sensors and switches have an electrical switch function programmed to operate at a specific pressure. They are used in fuel pumps to monitor system pressure, ensuring it remains within safe and optimal operating ranges for accurate dispensing and to prevent damage to equipment. These solutions consist of a sensing component and an electrical switch that opens or closes a contact at a specific pressure set point.

The calibration is paramount for maintaining operational reliability and accuracy. Incorrect calibration can lead to inaccurate pressure readings, affecting the performance of the fuel pump and associated systems, and potentially causing significant errors or equipment damage. The calibration process involves several steps:

- **Preparation and Safety:** The switch or sensor must be depressurized and isolated from the process and any controlling circuits to ensure safety
- **Pressure Application:** A slowly changing pressure ramp is applied to the switch using a calibrated pressure source (e.g., hand pump, precise pressure controller)
- **Operation Point Capture:** A tool is used to measure the switch terminals and capture the input pressure at the exact moment when the output state changes (i.e., when the switch opens or closes)
- **Adjustment and Verification:** The pressure switch or sensor's set point is adjusted until the contacts open and close at the desired pressure. The process is repeated to confirm accuracy and measure hysteresis (the difference between the switch point and reset point)

Here's how each Honeywell product is specifically used — and why it's selected — for calibrating fuel/gas pump systems.

During dispenser calibration, an **MLH Series Pressure Transducer** is installed in-line with the pump's discharge or suction line. As fuel is dispensed into the prover, the MLH outputs a continuous 4 mA to 20 mA (or voltage) signal proportional to real-time pressure. This signal is used by the calibration system to verify that pressure stays within the manufacturer's specified range, indicating proper flow conditions. MLH sensors offer rapid response (<2 ms), high accuracy (±0.25 %FS), and rugged all-metal design — ensuring consistent, reliable readings during dynamic flow. Their immunity to electromagnetic interference (MIL-STD 810C certified) makes them well-suited for environments near motors and control electronics





In calibration equipment, a **MIP Series Pressure Transducer** is coupled similarly — monitoring pump-side pressure during dispensing into a prover. Its analog or digital output feeds the calibration controller, enabling pressure tracking throughout the calibration cycle. This allows detection of pressure drops or spikes potentially affecting volume accuracy. Designed for rugged fuel system environments, MIP features all-stainless wetted parts, hermetic sealing, and digital-output options (like I²C/SPI) for embedded calibration setups. The high stability (±0.25 % long-term) and ability to withstand overpressure ensure that calibration remains accurate day after day, even under field conditions — proven compatibility with transporation media such as gasoline, diesel fuel, engine oil, coolants, and CNG also contribute to heavy-duty suitability.

As a switch option, during calibration, a **5000 Series Pressure Switch** is placed in the pump line and set to open or close at a specific threshold (e.g., cut off at 150 psi). As the calibration run completes and pressure reaches that set point, the switch actuates, signaling the calibration unit to stop dispensing — acting as a reliable hardware safeguard. These switches are factory-set but field-adjustable between 0.5 psi to 150 psi, compatible with hydrocarbons (fuel) via a Kapton diaphragm, and offer tight set-point repeatability and a compact sealed design. With a proof pressure of 500 psi, they robustly handle calibration scenarios without false triggers or failure — ensuring consistent cutoff and protecting against overpressure during meticulous calibration cycles.

Together, these devices offer a complete toolkit for calibrating fuel/gas pumps: accurate measurement, environmental robustness, and fail-safe protection.



USER INTERFACE AND FEEDBACK

Electromechanical switches are integral to the user interface of fuel dispensers, providing tactile input and critical status feedback.

User Input Buttons

The user interface of a fuel dispenser relies heavily on various electromechanical buttons for customer and operator interaction. These include:

- **Push to Start Panels:** These buttons initiate the fueling process after payment authorization. They are typically robust and designed for frequent public use
- **Grade Select Buttons:** Customers use these buttons to choose the desired fuel octane or grade

Status and Warning Indicators

Electromechanical switches also contribute to providing critical status and warning feedback to users and attendants.


- **Pilot Lights:** Some electromechanical switches include a small indicator light, known as a pilot light, which illuminates when the circuit is closed and the switch is in the "on" position. This light serves as a visual indicator to show whether a connected load, such as the pump motor, is powered on or off
- **Audible and Visual Alert Systems:** Beyond simple pilot lights, more sophisticated systems utilize electromechanical switches to activate warning signals. For example, a safety warning system reminds users to replace a fuel nozzle after dispensing fuel. This system is activated as the user removes the nozzle from its mount, triggering a limit switch. The switch, in turn, activates a control relay, which then simultaneously activates both a visual indicator (e.g., a light) and an audio indicator (e.g., a speaker). These evident reminders significantly reduce the chances of a motorist driving off with the nozzle still attached, preventing damage and potential hazards. The design of these systems ensures that when the nozzle is properly docked, the limit switch is in an open position, keeping the warning indicators inactive

In a fuel/gas pump application, Honeywell AML Series indicators play a vital role in delivering real-time status and alerts to both operators and maintenance personnel.

MICRO SWITCH AML indicators — like the **AML 41/42 pushbutton-style and AML 45/59 LED annunciators** — are panel-mounted signal lights that illuminate or flash to indicate critical pump statuses such as "Pump Ready", "Prime in Progress", or "Fault Detected." Mounted prominently on the dispenser or calibration rig, they provide immediate visual cues through LEDs or incandescent/neon lamps.



MICRO SWITCH AML 41/42 Pushbutton



MICRO SWITCH AML 45/49 LED Annunciator

This enables attendants to quickly confirm whether the system is operating correctly or needs attention.

Many AML devices double as electromechanical switches: they include fine or gold-plated contacts rated for logic and power load. These indicators can also act as hardwired inputs into a dispenser's control system — triggering relays or PLC logic when pressed or illuminated. For instance, an illuminated AML switch could reset an alarm or manually initiate dispenser calibration, while its contacts inform the ECU of user actions.

High visibility, front-panel mounting: Low-profile but intuitive, they ensure critical feedback is unmissable to station personnel. AML Series also offer a choice of illumination types (LED, incandescent, neon) and colors help differentiate alert types (e.g. green for ready, red for fault). Modular button sizes, engraved legends, and optional key-actuated or maintained-action switches allow custom-tailored user interfaces directly tied to pump functions

Basic switches may also be used for status and warning indicators.

MICRO SWITCH V15W Watertight Miniature Basic Switch can be mounted to detect physical events — such as door closure or calibration unit engagement. For instance, when a service door is closed, the plunger is pressed, actuating the switch to notify the control system that the dispenser is secured and ready for operation or maintenance. Its IP67 sealing ensures reliable operation in environments contaminated with fuel vapors, moisture, or dust. With ratings up to 10 A, it handles both logic-level signals and moderate loads — ideal for triggering indicator lights or control relays. The vast actuator and termination options make it simple to integrate into varied mechanical linkages in fuel pump assemblies.

MICRO SWITCH ZD Series Sealed Subminiature Snap-Action Switch fits neatly into dispenser panels to detect small mechanical events (e.g., status, hose coupling secured). Its rapid snap-action ensures fast, reliable transition between contacts — changing system state in real time. This signal can drive warning LEDs or feed into the microcontroller to log status changes or errors. With its compact form, the switch is rated to IP67 (when pre-wired) and supports both logic (gold-plated contacts) and modest power-duty signals (up to 3 A), which is handy for control circuits within the dispenser. Its subminiature size allows deployment in tight spaces near valves or sensor arrays.

MICRO SWITCH ZW Series Sealed Subminiature Basic Switches are ideal for functions requiring more electrical capacity — such as monitoring high-pressure relief valve actuation or pump motor interlock positions. When a threshold is crossed — say, the valve opens — the switch's plunger moves, signaling a status change that can illuminate alarms or prevent further operation. With IP67 sealing and up to 6 A/250 Vac capability, the ZW switch handles higher currents and harsher environments — fuel exposure, vibration, and temperature extremes. The option for silver contacts ensures robust power switching, while gold-plated options provide noise-free logic feedback.





CONCLUSION

The modern fuel dispenser is an example of sophisticated engineering, seamlessly integrating electronic control with robust mechanical and hydraulic systems. This application note details the intricate anatomy of these dispensers, highlighting their dual architecture of an electronic head for control and a mechanical section for physical fuel handling. The consistent observation of this design approach underscores a fundamental principle in industrial systems: the electronic brain directs the mechanical brawn, with precise feedback and control mechanisms bridging the two.

Within this complex ecosystem, electromechanical switches emerge as indispensable components, serving as the critical interface between physical actions and electrical responses. From initiating fuel flow via nozzle state detection to precisely measuring dispensed volume through rotary encoders, and from implementing critical safety shut-offs to providing tactile user feedback, these switches are pervasive. Their deployment reflects a deliberate engineering strategy that balances cost, simplicity, and the paramount need for durability and environmental resilience in a hazardous, high-traffic environment. The trade-offs between simpler, lower-cost mechanical switches and more robust, higher-precision electronic alternatives are carefully managed to optimize performance for each specific function.

Furthermore, the extensive array of safety and environmental control systems, many of which rely on electromechanical switches, emphasizes a profound commitment to redundancy and fail-safe design. Features such as automatic nozzle shut-offs, breakaway valves, emergency stop buttons, leak detection, and safety interlocks collectively form a multi-layered defense. This approach prioritizes preventing harm and minimizing risk over continuous operation in the face of a fault, extending the definition of safety to include environmental protection.

Finally, the necessity for regular calibration of electromechanical components, particularly those involved in metering and pressure regulation, highlights their role as active elements in maintaining system accuracy and integrity throughout their operational lifecycle. This ongoing requirement dictates that fuel dispenser designs must facilitate safe and precise access for maintenance, underscoring the long-term operational considerations embedded in their engineering. In essence, electromechanical switches are not merely discrete components but are fundamental enablers of the functionality, accuracy, and safety that define modern fuel dispensing systems.



⚠WARNING IMPROPER INSTALLATION

- Consult with local safety agencies and their requirements when designing a machine control link, interface and all control elements that affect safety.
- Strictly adhere to all installation instructions.

Failure to comply with these instructions could result in death or serious injury.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While Honeywell may provide information or engineering support for its products through Honeywell personnel, literature and website, it is the buyer's sole responsibility to determine the suitability of the Honeywell product(s) for the buyer's requirements.

Specifications may change without notice. The information we supply is believed to be accurate as of this writing. However, Honeywell assumes no responsibility for its use.

For more information

Honeywell Sensing Solutions services its customers through a worldwide network of sales offices and distributors. For application assistance, current specifications, pricing, or the nearest Authorized Distributor, visit our website or call:

USA/Canada	+1 302 613 4491
Latin America	+1 305 805 8188
Europe	+44 1344 238258
Japan	+81 (0) 3-6730-7152
Singapore	+65 6355 2828
Greater China	+86 4006396841

Honeywell Sensing Solutions
830 East Arapaho Road
Richardson, TX 75081
www.honeywell.com

001051-1-EN | 1 | 10/25
© 2025 Honeywell International Inc. All rights reserved.

Honeywell