



Z-Perform 1000D Removable

Matte-finished, direct thermal paper label

Z-Perform 1000D Removable is a matte-finished, direct thermal paper label that offers exceptional performance and versatility. Engineered with a BPA-free face stock, it produces high-contrast black images when used with recommended Zebra printers. A key advantage of this media is its direct thermal printing capability, which eliminates the need for a ribbon, thereby streamlining your inventory to a single stock item. The label is designed for reliable adhesion and clean removability, ensuring it can be peeled off a wide variety of surfaces without leaving residue behind.



Designed for indoor environments, this paper label is an excellent choice for applications requiring cold temperature resistance. The adhesive is formulated for a minimum application temperature of +5°C and can withstand a service temperature range from -10°C to 80°C after application. However, it is important to note that Z-Perform 1000D Removable is not recommended for applications that involve long-term exposure to direct sunlight, extreme heat, or for use on PVC surfaces. With a total thickness of 126 microns, it provides a durable solution for many labeling needs.

The suggested applications for Z-Perform 1000D Removable are broad, making it a flexible choice for various industries. It is ideal for indoor general-purpose labeling, food labeling, product identification, and tracking work in progress. In retail settings, it serves perfectly as a removable solution for shelf-edge, product, and price labeling. It is also highly effective for temporarily labeling boxes, pallets, shelves, and tote bins. Compatible with Zebra's mobile, desktop, mid-range, and high-performance thermal printers, this label has an expected indoor lifespan of up to one year.

Z-Perform 1000D Removable—Offers exceptional performance and versatility

For more information, please visit www.zebra.com/supplies

Specifications

Technical Specifications	
Facestock	Matte white uncoated thermal imaging paper 66 microns
Adhesive	Removable rubber adhesive 13 microns
Liner	60gsm glassine liner 47 microns
Total Thickness (+/- 10%)	126 microns
Environment	Indoor use; cold temperature compatible
Temperature Performance	
Minimum Application Temperature ¹	41°F/ 5°C
Service Temperature Range ²	14°F to 176°F/ -10°C to 80°C
Recommended Printers and Ribbons	
Printers	Mobile, desktop, mid-range and high-performance thermal printers
Ribbons	N/A
Additional Information	
Recommended Storage Conditions	6 months duration when stored at 20°C at 50% RH
Expected Life Span in Application	Indoor use, for up to 1 year
Sample Part Number	SAMPLE40762.
Product Performance and Suitability	
The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.	
Footnotes	
1. When the label is applied, the environment and surface should be above this temperature. 2. Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range.	

Markets and Applications

- Indoor general purpose labelling and food labelling
- Labelling of most packaging materials
- Removable shelf-edge labelling, product and price labelling in retail
- Product Identification
- Work in progress labelling
- Removable labels for boxes, pallets, shelves or tote bins